CE

UNILIN

DECLARATION OF PERFORMANCE

XTROLINER SUPERIOR PERFORMANCE PIR INSULATION

XO/UF

1. **Product Type**
   Unique identification code of the product type:

   Xtroliner Underfloor

2. **Type**
   Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

   Batch No on board

3. **Intended Use**
   Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

   Thermal Insulation for Buildings

4. **Name, Registered Trade Name**
   Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

   Unilin Insulation Ireland Ltd
   Liscarton Industrial Estate
   Kells Road, Navan
   Co. Meath, Ireland
   C15 NP79

5. **Contact Address**
   Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

   Not relevant (see 4)

6. **AVCP**
   System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

   System 1 - Reaction to Fire
   System 3 - Other Characteristics

7. **Notified Body (hEN)**
   In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

   EN 13165:2012+A2:2016
   Notified Body: FIW/Efectis
   Notified Body No: 0751/1812
   Performed type testing under systems 1 and 3 and issued certificate of constancy and test reports.

8. **Notified Body (ETA)**
   In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

   Not relevant (see 7)

Unilin Insulation Ireland Ltd
Liscarton Industrial Estate, Kells Road, Navan, Co. Meath Ireland, C15 NP79

T +353 (0) 46 906 6000
F +353 (0) 46 906 6090
E info.ui@unilin.com

CE

UNILIN

DECLARATION OF PERFORMANCE

9. Declared Performance

Essential Characteristics	Performance	Test Standard	Harmonised Standard
Thermal Conductivity	0.021	EN 12667:2001	EN 13165:2012 +A2:2016
Reaction to Fire	Euroclass C s2 d0	EN 13501-1-2018	
Thickness	T2	EN 823:2103	
Length & Width	<1000mm: ± 5mm 1000 to 2000mm: ± 7,5mm 2001 to 4000mm: ± 10mm >4000mm: ± 15mm	EN822:2013	
Squareness	≤ 5mm/m	EN824:2103	
Flatness	Length: ≤ 2,5m Area ≤ 0,75m²: Deviation ≤ 5mm Area > 0,75m²: Deviation ≤ 10mm	EN 825:2103	
Dimensional Stability	DS (70,90)3	EN 1604:2103	
Dimensional Stability	DS (-20,-)2	EN 1604:2103	
Compressive Strength	CS (10\Y) 150	EN 826:2103	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Aidan Doyle, General Manager
Unilin Insulation Ireland Ltd.
01-06-2026



Unilin Insulation Ireland Ltd
Liscarton Industrial Estate, Kells Road, Navan, Co. Meath Ireland, C15 NP79

T +353 (0) 46 906 6000
F +353 (0) 46 906 6090
E info.ui@unilin.com