



SPECIFICATION CLAUSE

STONEWOOL NON-COMBUSTIBLE INSULATION

Ventilated Rainscreen Cladding

SW/RS

The rainscreen insulation shall be Unilin Insulation Stonewool __ __ mm manufactured to EN 13162:2012+A1:2015. The Unilin Insulation Stonewool SW/RS __ __ mm with a Declared Lambda value of 0.036 W/mK to achieve a U-Value of __ __ W/m²K for the wall element. To be installed in accordance with instructions issued by the facade engineer.

Refer to NBS clause P10 42, P10 217, H11 110. Uniclass Pr 25 57 06 56.

Insulation

Semi rigid mineral wool slab

Standard

BS EN 13162:2012+A1:2015

Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

Supplier

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033
F 0371 222 1044
E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000
F 04690 66090
E info.ui@unilin.com

unilininsulation.ie

Manufacturer

Ravaber Yapı Ürünleri San. Ve Tic. A.S. Org. San. Böl. 20.cad. No:54 Kayseri

Product Reference

Unilin Insulation StoneWool SW/RS

Face Size

1200mm x 600mm

Edge Profile

Square Edge

Thickness

50mm / 75mm / 100mm / 125mm / 150mm

Other sizes available dependent on quantity & lead time.