



# SPECIFICATION CLAUSE

**ECO360** BIO-ENHANCED  
PIR INSULATION

## Partial Fill Cavity Walls

ECO/CW

The partial fill cavity wall insulation shall be ECO360 Cavity Wall ECO/CW manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid modified Polyisocyanurate (PIR) core between textured foil facings and engineered shiplap jointing. The ECO/CW \_\_\_mm with a declared Lambda value of 0.020 W/mK to achieve a U-Value of \_\_\_W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 155, F30 12. Uniclass 25 71 63 66.

### Insulation

Modified Polyisocyanurate Rigid Foam

### Insulation

BS EN 13165:2012+A2:2016

### Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

### Manufacturer

#### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033  
**F** 0371 222 1044  
**E** info.ui@unilin.com

unilininsulation.co.uk

#### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000  
**F** 04690 66090  
**E** info.ui@unilin.com

unilininsulation.ie

### Product Reference

Unilin Insulation ECO360 Cavity Wall ECO/CW  
Partial Fill Cavity Wall Insulation

### Face Size

1200mm x 450mm

### Edge Profile

Rebated on all four edges

### Thickness

100mm / 110mm