



SPECIFICATION CLAUSE

ECO360 BIO-ENHANCED PIR INSULATION

Pitched Roofs

ECO/MA (ROOFS)

The pitched roof insulation shall be ECO360 ECO/MA Roofs manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid modified Polyisocyanurate (PIR) core between textured foil facings. The ECO/MA ___mm with a declared Lambda value as low as 0.020 W/mK to achieve a U-Value of ___W/m²K for the roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 140, K11 695, K11 55, P10 50, P10 15. Uniclass 25 71 63 66.

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165:2012+A2:2016

Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation ECO360 ECO/MA
Pitched Roof Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Square Edge

Thickness

50mm / 100mm / 125mm / 150mm