



SPECIFICATION CLAUSE



HYTHERM HD WHITE

The floor insulation shall be Unilin Insulation Hytherm HD White underfloor insulation boards manufactured to EN 13163:2012+A2:2016 by Unilin Insulation, consists of rigid polystyrene boards cut from molded blocks of EPS. The Unilin Insulation Hytherm HD White __ mm with a Agrément declared Lambda value of 0.035 W/mK to achieve a U-Value of __ W/m²K for wall, floor or roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause E20 200, E20 30, J31 331. Uniclass Pr 25 71 63 26.

Insulation

Expanded Polystyrene

Standard

BS EN 13163:2012+A2:2016

Certification

- BBA Certification No. 24/7224
- NSAI Certification No. 04/0022
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Hytherm HD White

Length

1200mm / 1800mm / 2400mm

Width

600mm & 1200mm

Other sizes available dependent on quantity & lead time.

UK/IRL_HYTHERM_HDWHITE_SC_May2025_v2

Edge Profile

Square Edge

Thickness

25mm / 30mm / 35mm / 40mm / 45mm / 50mm / 60mm / 70mm / 75mm / 80mm / 90mm / 100mm / 125mm / 150mm