



# SPECIFICATION CLAUSE

## SAFE-R PHENOLIC INSULATION

### Steel & Timber Frame

SR/FB

The wall insulation shall be Safe-R SR/FB manufactured to EN 13166:2012+A1:2015 by Unilin Insulation, comprising of a rigid Phenolic core between composite foil facings. The Safe-R SR/FB \_\_ \_mm with Agrément declared Lambda value as low as 0.020W/mK to achieve a U-Value of \_\_ \_W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause H92 776, H20 150. Uniclass Pr 25 71 63 59.

#### Insulation

Phenolic Rigid Foam

#### Standard

BS EN 13166:2012+A1:2015

#### Certification

- BBA Certification No. 23/6884
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

#### Product Reference

Unilin Insulation Safe-R SR/FB Steel & Timber Frame Insulation

#### Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

#### Edge Profile

Square Edge

#### Thickness

50mm / 60mm / 75mm / 80mm / 100mm / 120mm