



SPECIFICATION CLAUSE

CAVITYTHERM BUILT IN FULL FILL WALL INSULATION

Cavity Tray Channel

CT/ACC/CTC

The cavity tray channel insulation shall be CavityTherm CT/ACC/CTC Cavity Tray Channel 60mm thick, 1200mm length, manufactured to EN 13165 by Unilin Insulation, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings, with a Lambda value of 0.022 W/mK, suitable for ___mm cavity. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 12, F30 155.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation CavityTherm CT/ACC/CTC
Cavity Tray Channel Insulation