



SPECIFICATION CLAUSE

ECO360 BIO-ENHANCED PIR INSULATION

Partial Fill Cavity Walls

ECO/CW

The partial fill cavity wall insulation shall be ECO360 Cavity Wall manufactured to EN 13165 by Unilin Insulation, comprising a rigid modified Polyisocyanurate (PIR) core with textured robust low emissivity foil facings and engineered shiplap jointing. The ECO360 Cavity Wall ___mm with a declared Lambda value of 0.020 W/mK to achieve a U-Value of ___W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 155, F30 12.

Insulation

Modified Polyisocyanurate Rigid Foam

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation ECO360 Partial Fill Cavity Wall Insulation

Thickness

110mm / 110mm

Face Size

1200mm x 450mm