



SPECIFICATION CLAUSE

ECO360 BIO-ENHANCED PIR INSULATION

Solid & Suspended Floors

ECO/MA (FLOORS)

The floor insulation shall be ECO360 MA Floors manufactured to EN 13165 by Unilin Insulation, comprising a rigid modified Polyisocyanurate (PIR) core with textured robust low emissivity foil facings. The ECO360 MA_ _ _mm with a declared Lambda value as low as 0.020 W/mK to achieve a U-Value of _ _ _W/m²K for the floor element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause M10 290, M10 40, M13 260 M13 40.

Insulation

Modified Polyisocyanurate Rigid Foam

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation ECO360 MA Under Floor Insulation

Edge Profile

Square Edge

Face Size

2400mm x 1200mm

Thickness

100mm / 125mm / 150mm

Other sizes available dependent on quantity & lead time.