



SPECIFICATION CLAUSE

XTROLINER SUPERIOR PERFORMANCE PIR INSULATION*

Partial Fill Cavity Walls

XO/XWP

The partial fill cavity wall insulation shall be XtroWall XO/XWP/110 manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid Polyisocyanurate (PIR) core between composite foil facings and engineered shiplap jointing. The XtroWall Plus 110mm with a declared Lambda value of 0.020 W/mK to achieve a U-Value of 0.15 W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 155, F30 12. Uniclass Pr 25 71 63 66.

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165:2012+A2:2016

Certification

- NSAI Certification No. 20/0422
 - BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
-

Manufacturer

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan,
Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation XtroWall Plus Partial Fill
Cavity Wall Insulation

Face Size

1200mm x 450mm

Edge Profile

Rebated on all four edges

Thickness

110mm

*The reference to superior performance relates to the product or ranges thermal conductivity or fire performance or a combination of both, when compared to our Thin-R range.