

SPECIFICATION CLAUSE

SAFE-R PHENOLIC INSULATION

Steel & Timber Frame

SR/FB

The wall insulation shall be Safe-R SR/FB manufactured to EN 13166 by Unilin Insulation, comprising a rigid Phenolic core between low emissivity foil facings. The Safe-R SR/FB ___mm with Agrément declared Lambda value as low as 0.020W/mK to achieve a U value of ___W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 12, F30 155, K10 15, K10 205, K10 25, P10 180.

Insulation

Phenolic Rigid Foam

Standard

BS EN 13166

Certification

- BBA Certification No. 10/4803
 - BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Safe-R SR/FB Steel & Timber Frame Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Straight Edge

Thickness

50mm / 60mm / 75mm / 80mm / 100mm / 120mm