

SPECIFICATION CLAUSE

SAFE-R PHENOLIC INSULATION

Soffit Application (Soffit Plus)

SR/STP

The soffit insulation shall be Safe-R SR/STP ___mm manufactured to EN 13166 by Unilin Insulation, comprising a rigid Phenolic core between low emissivity foil facings bonded to 6mm building panel. The Safe-R SR/STP ___mm with Agrément declared Lambda value as low as 0.020W/mK (Phenolic only) to achieve a U-Value of ___W/m²K for the soffit element to be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 185, P10 217.

Insulation

Phenolic Rigid Foam

Standard

BS EN 13166

Certification

- BBA Certification No. 10/4803
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Safe-R SR/STP Soffit Plus Insulation

Edge Profile

Straight Edge

Face Size

2400mm x 1200mm

Thickness

56mm / 66mm / 76mm / 81mm / 86mm / 106mm / 126mm

Other sizes available dependent on quantity & lead time.