



SPECIFICATION CLAUSE

SAFE-R PHENOLIC INSULATION

Drylining Walls Mechanically Fixed

SR/TB-MF

The insulated drylining wall insulation shall be Safe-R SR/TB-MF manufactured to EN 13166 by Unilin Insulation, comprising a rigid Phenolic core between composite foil/glass tissue facings. The SR/TB-MF ___mm with Lambda value as low as 0.020 W/mK (Phenolic only), bonded to 12.5mm plasterboard to EN 13950, achieving a U-Value of ___W/m²K for the wall element. The insulated drylining plasterboard SR/TB-MF shall be mechanically fixed to battens, or proprietary system in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause K10 205, K10 15, K10 245, K10 25.

Insulation

Phenolic Rigid Foam

Standard

EN 13166, EN 13950

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Safe-R SR/TB-MF
Thermal Liner Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Plasterboard – Tapered, Phenolic – Square Edge

Thickness

25mm / 40mm / 50mm / 60mm / 75mm / 80mm / 100mm