SPECIFICATION CLAUSE

ACCESSORIES CAVITY CLOSER

Wall Cavity Closer

CLOSE-R

The partial/full fill cavity wall cavity closer insulation shall be Unilin Insulation Close-R manufactured to EN 13165 :2012+ A2:2016 (insulation component only) by Unilin Insulation, comprising of a rigid PVC-U Outer Profile with encapsulated rigid Polyisocyanurate (PIR) core between composite foil facings suitable for _ _ _mm cavity. To be installed in accordance with instructions issued by Unilin Insulation.

Note EN 13165 :2012+ A2:2016 applies to the PIR insulation component only, not the complete Close-R product

Refer to NBS clause F30 180, F30 18
Uniclass Pr 35 90 50 64

Insulation
Polyisocyanurate Rigid Foam

Standard
EN 13165 :2012+ A2:2016
(PIR insulation component only)

Certification
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd
Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033
F 0371 222 1044
E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd
Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000
F 04690 66090
E info.ui@unilin.com

unilininsulation.ie

Product Reference
Unilin Insulation Closer-R Cavity Wall Closer
Panel Insulation