

# SPECIFICATION CLAUSE

---

## FLAT ROOF TOTAL FLAT ROOF SOLUTIONS

---

### Single Ply Fully Adhered Systems

TR/MG

The tapered roof insulation shall be Unilin Insulation Thin-R TR/MG\_ \_ \_mm thick manufactured to EN 13165:2012+A2:2016 by Unilin Insulation comprising of a rigid Polyisocyanurate (PIR) core between glass fibre facings with a Agrément declared Lambda value as low as 0.024 W/mK. The tapered roof insulation shall be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause J42 420, J42 10, J42 430. Uniclass 25 71 63 66.

---

#### Insulation

Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165:2012+A2:2016

#### Certification

- BBA Certification No. 24/7235
  - BS EN ISO 9001 Quality Management System
  - BS EN ISO 14001 Environmental Management System
  - ISO OHSMS 45001 Health and Safety Management System
- 

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

---

#### Product Reference

Unilin Insulation Thin-R TR/MG  
Tapered Roof Insulation

#### Face Size

1200mm x 1200mm

Other tapers available dependent on quantity & lead time.

#### Edge Profile

Square Edge

#### Thickness

30-50mm / 50-70mm / 70-90mm / 90-110mm