



# SPECIFICATION CLAUSE

## XTROLINER SUPERIOR PERFORMANCE PIR INSULATION\*

### Sarking Warm Roof Construction

XO/SK

The pitched roof Sarking insulation shall be XtroLiner XO/SK manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid Polyisocyanurate (PIR) core between textured foil facings and engineered (T&G) jointing. The XtroLiner XO/SK \_\_ mm with a Lambda value of 0.021 W/mK to achieve a U-Value of \_\_ W/m<sup>2</sup>K for the roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 15, P10 140, P10 50, K11 695, K11 55. Uniclass Pr 25 71 63 66.

#### Insulation

Modified Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165:2012+A2:2016

#### Certification

- BBA Certification No. 23/6874
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

#### Product Reference

Unilin Insulation XtroLiner XO/SK Pitched Roof Sarking Insulation

#### Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

#### Edge Profile

Square Edge

#### Thickness

50mm / 75mm / 100mm / 125mm

\*The reference to superior performance relates to the product or ranges thermal conductivity or fire performance or a combination of both, when compared to our Thin-R range.