

# SPECIFICATION CLAUSE

---

## **XTROLINER** SUPERIOR PERFORMANCE PIR INSULATION

### Steel & Timber Frame Systems

XO/FB

The wall insulation shall be XtroLiner XO/FB manufactured to EN 13165 by Unilin Insulation, comprising a rigid modified Polyisocyanurate (PIR) core with textured robust low emissivity foil facings. The XtroLiner XO/FB\_ \_ \_mm with a Agrément declared Lambda value of 0.021 W/m K to achieve a U value of \_ \_ \_W/m<sup>2</sup>K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 12, F30 155, K10 15, K10 205.

---

#### Insulation

Modified Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165

#### Certification

- BBA Certification No. 12/4956
  - BS EN ISO 9001 Quality Management System
  - BS EN ISO 14001 Environmental Management System
  - ISO OHSMS 45001 Health and Safety Management System
- 

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

---

#### Product Reference

Unilin Insulation XtroLiner XO/FB Steel & Timber Frame Insulation

#### Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

#### Edge Profile

Straight Edge

#### Thickness

50mm / 60mm / 75mm / 80mm / 100mm / 120mm