



SPECIFICATION CLAUSE

XTROLINER SUPERIOR PERFORMANCE PIR INSULATION

Soffit Application

XO/STP

The soffit insulation shall be XtroLiner XO/STP ___mm manufactured to EN 13165 by Unilin Insulation, comprising a rigid modified Polyisocyanurate (PIR) core with a Agrément declared Lambda value of 0.021 W/mK and textured robust low emissivity foil facings with 6mm building panel. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 185, P10 217.

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BBA Certification No. 12/4956
 - BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation XtroLiner XO/STP Soffit Insulation

Face Size

2400mm x 1200mm

Edge Profile

Straight Edge

Thickness

56mm / 66mm / 76mm / 81mm / 86mm / 106mm / 126mm

Other sizes available dependent on quantity & lead time.