



SPECIFICATION CLAUSE

THIN-R^{PIR} INSULATION

Partial Fill Cavity Walls

XT/CW (T&G)

The partial fill cavity wall insulation shall be Thin-R XT/CW T&G manufactured to EN 13165 by Unilin Insulation, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings. The Thin-R XT/CW T&G ___ mm with an Agrément declared Lambda value of 0.022 W/mK to achieve a U-Value of ___ W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 155, F30 12.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BBA Certification No. 08/4613
 - BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Thin-R XT/CW T&G Partial Fill Cavity Wall Insulation

Face Size

1200mm x 450mm

Other sizes available dependent on quantity & lead time.

Edge Profile

T&G all four edges

Thickness

40mm / 50mm / 60mm / 70mm / 80mm / 100mm / 110mm