



SPECIFICATION CLAUSE

THIN-R^{PIR} INSULATION

Insulated Loft Decking

XT/WALK-R

The ceiling insulation shall be Unilin Insulation Thin-R Walk-R manufactured to EN 13165 by Unilin Insulation, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings bonded to OSB Board. The Walk-R 86mm with __ __mm Mineral Wool to achieve a U-Value of __ __W/m²K for the roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 10, P10 135.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Thin-R Walk-R Ceiling Insulation

Face Size

1200mm x 600mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Available as Straight Edge or T&G (Insulation only)

Thickness

86mm