

Thermal Ply High Performance PIR & Plywood Composite for Flat Roofs

FR/TP

_									
	Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M²/Plt	Weight (per product piece)
	FR/TP/055.5/PL5.5/SP06	XT Roof T-Ply 2400x1200x56 (Ply 5.5)	Straight	55.5	20	57.60	2	115.20	23.00
	FR/TP/075.5/PL5.5/SP06	XT Roof T-Ply 2400x1200x76 (Ply 5.5)	Straight	75.5	15	43.20	2	86.40	25.00
	FR/TP/095.5/PL5.5/SP06	XT Roof T-Ply 2400x1200x96 (Ply 5.5)	Straight	95.5	11	31.68	2	63.36	27.00
	FR/TP/105.5/PL5.5/SP06	XT Roof T-Ply 2400x1200x106 (Ply 5.5)	Straight	105.5	10	28.80	2	57.60	28.00
	FR/TP/115.5/PL5.5/SP06	XT Roof T-Ply 2400x1200x116 (Ply 5.5)	Straight	115.5	10	28.80	2	57.60	28.00

^{*}Weight (rounded up to the nearest kg)

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details. All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load



^{*}Thickness includes 6mm plywood