



SPECIFICATION CLAUSE

ACCESSORIES

Cavity Closer

SAFE-R CLOSE-R

The cavity closer shall be Unilin Insulation Safe-R Cavity Closer comprising of a rigid Phenolic core between composite foil facings manufactured to EN 13166:2012+A1:2015 with a declared Lambda values as low as 0.020W/mK and mineral wool manufactured to EN 13162:2012+A1:2015, with a declared Lambda value as low as 0.037 W/mK wrapped in a protective red sleeve to achieve a minimum 4-hour fire resistance tested to EN 1366-4. To be installed in accordance with instructions issued by Unilin Insulation.

Uniclass 25 71 63 59.

Insulation

Phenolic Rigid Foam & Mineral Wool

Standard

BS EN 13166:2012+A1:2015, BS EN 13162:2012+A1:2015

Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033
F 0371 222 1044
E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000
F 04690 66090
E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Safe-R Cavity Closer

Face Size

200mm x 1200mm

Edge Profile

Square Edge

Thickness

100mm / 125mm / 150mm