



SPECIFICATION CLAUSE

XPS EXTRUDED POLYSTYRENE
INSULATION

Solid Ground Floors

XPS 300

The insulation shall be Unilin Insulation XPS 300 manufactured to EN 13164:2012 by Soprema, comprising of Extruded Polystyrene. The Unilin Insulation XPS 300 __ __mm with declared Lambda value as low as 0.033 W/mK is to achieve a U-Value of __ __W/m²K for the floor, wall or roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause J42 414, J42 440, E20 200, K11 215, K11 295, Q37 310, J42 10. Uniclass Pr 25 71 63 29.

Insulation

Extruded Polystyrene

Standard

BS EN 13164:2012

Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

Supplier

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire,
UK, S42 5UY

T 0371 222 1033
F 0371 222 1044
E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan,
Co. Meath, Ireland, C15 NP79

T 04690 66000
F 04690 66090
E info.ui@unilin.com

unilininsulation.ie

Manufacturer

SOPREMA

14 rue de Saint-Nazaire, CS 60121,
67025 Strasbourg Cedex, France

E info@soprema.ie

soprema.ie

Product Reference

Unilin Insulation XPS 300 Under Floor Insulation

Face Size

1250mm x 600mm

Edge Profile

Rebated on all four edges

Thickness

30mm / 40mm / 50mm / 60mm / 80mm /
100mm / 120mm / 140mm / 160mm

Other sizes available dependent on quantity & lead time.