



# SPECIFICATION CLAUSE

---

## RAFTERLOC

---

### Pitched Roof Board

#### XT/RLOC

The pitched roof insulation shall be Unilin Insulation Thin-R XT/RLOC manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid Polyisocyanurate (PIR) core between composite foil facings. The Thin-R XT/RLOC \_\_\_ mm with an Agrément declared Lambda value of 0.023 W/mK to achieve a U-Value of \_\_\_ W/m<sup>2</sup>K for the roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 140, P10 15, P10 50. Uniclass 25 71 63 66.

---

#### Insulation

Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165:2012+A2:2016

#### Certification

- NSAI Certification No. 08/0324
  - BS EN ISO 9001 Quality Management System
  - BS EN ISO 14001 Environmental Management System
- 

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033  
**F** 0371 222 1044  
**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000  
**F** 04690 66090  
**E** info.ui@unilin.com

unilininsulation.ie

---

#### Product Reference

Unilin Insulation Thin-R XT/RLOC  
Pitched Roof Insulation

#### Face Size

1200mm x 370mm

Other sizes available dependent on quantity & lead time.

#### Edge Profile

Square Edge

#### Thickness

100mm / 125mm / 150mm