SR/TBFL-MF

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M²/Plt	Weight (per product piece)
SR/TBFLMF/065/GYF15/SP06	SR TBoard FireLineMF 2400x1200x65(PB15F)	Straight	65	15	43.20	2	86.40	39.00
SR/TBFLMF/075/GYF15/SP06	SR TBoard FireLineMF 2400x1200x75(PB15F)	Straight	75	15	43.20	2	86.40	40.00
SR/TBFLMF/085/GYF15/SP06	SR TBoard FireLineMF 2400x1200x85(PB15F)	Straight	85	13	37.44	2	74.88	41.00
SR/TBFLMF/095/GYF15/SP06	SR TBoard FireLineMF 2400x1200x95(PB15F)	Straight	95	12	34.56	2	69.12	42.00
SR/TBFLMF/105/GYF15/SP06	SR TBoard FireLineMF 2400x1200x105(PB15F)	Straight	105	10	28.80	2	57.60	43.00

*Weight (rounded up to the nearest kg)
*Total thickness of composite panel provided

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details.
All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load

UNILIN

Unilin Insulation Ireland Ltd
Liscarton Industrial Estate, Kells Road
Navan, Co. Meath, Ireland, C15 NP79

t. +353 (0) 46 906 6000
e. info.ui@unilin.com

unilininsulation.ie