THIN-R PIR INSULATION

Drylining Walls Fixed With Adhesive Dabs

XT/TL

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M²/Plt	Weight (per product piece)
XT/TLDD/037.5/GYP12.5/SP62	XT T-Liner DD 2438x1200x37.5 (PB 12.5S)	Straight	37.5	1	2.93	40	117.02	28.00
XT/TLDD/050.5/GYP12.5/SP62	XT T-Liner DD 2438x1200x50.5 (PB 12.5S)	Straight	50.5	1	2.93	35	102.40	20.00
XT/TLDD/062.5/GYP12.5/SP62	XT T-Liner DD 2438x1200x62.5 (PB 12.5S)	Straight	62.5	1	2.93	25	73.14	30.00
XT/TLDD/072.5/GYP12.5/SP62	XT T-Liner DD 2438x1200x72.5 (PB 12.5S)	Straight	72.5	1	2.93	20	58.51	31.00
XT/TLDD/082.5/GYP12.5/SP62	XT T-Liner DD 2438x1200x82.5 (PB 12.5S)	Straight	82.5	1	2.93	20	58.51	32.00
XT/TLDD/092.5/GYP12.5/SP62	XT T-Liner DD 2438x1200x92.5 (PB 12.5S)	Straight	92.5	1	2.93	15	43.88	33.00

*Weight (rounded up to the nearest kg)
*Total thickness including plasterboard

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details.
All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load

UNILIN

Unilin Insulation Ireland Ltd
Liscarton Industrial Estate, Kells Road
Navan, Co. Meath, Ireland, C15 NP79

t. +353 (0) 46 906 6000
e. info.ui@unilin.com

unilininsulation.ie